NSN 5905-01-061-5558

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-061-5558

Section Quantity:
2
Body Style: Cylindrical bushing mounted
Cylindrical bushing mounted Poliability Indicators
Reliability Indicator:
Not established Redu Diemeter
Body Diameter: 1.094 inches
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.266 inches
Shaft Style:
Round, slotted Actuator Tyron
Actuator Type:
Single shaft Nonturn Device Location:
At 9 oclock Nonturn Device Radius:
0.531 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
500.0 ohms all sections
Rotary Actuator Travel In Angular Deg: Between 309.0 and 320.0
Resistance Tempurature Characteristic Range Per Section In Percent: -3.0/±0.0 -55 degrees calsius all sections and -5.0/±10.0 -25 degrees calsius all sections are calsius all sections and -5.0/±10.0 -25 degrees calsius all sections are calsius
-3.0/+0.0 -55 degrees celsius all sections and -5.0/+10.0 -25 degrees celsius all sections and -5.0/+10.0 25 degrees celsius all sections and

120.0 all sections

+0.0/+3.0 120 degrees celsius all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

NSN 5905-01-061-5558

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
2.0 free air all sections
Resistance Tolerance Per Section In Percent:
10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Test Data Document:
31349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Ferminal Type And Quantity:
Stab, solder lug
Specification Data:
31349-mil-r-94/6 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No.