

View Online at <https://aerobasegroup.com/nsn/5905-01-061-9214>

**Section Quantity:**

3

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**First Flat Length:**

0.375 inches

**Flat Height:**

0.219 inches

**Body Diameter:**

0.500 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.906 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

0.450 inches

**Shaft Style:**

Round, flatted

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

120.0

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

360.0

**Switch Operating Position:**

Any position of rotation travel

**Switch Contact Arrangement:**

Double pole, single throw, normally open

**Screw Thread Diameter:**

0.190 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

20.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

20.0 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

360.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 all sections

**Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Actuator Travel Control Feature:**

Continuous motion

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

55.0 all sections

**Switch Current Type And Rating In Amps:**

1.000 ac

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0