

View Online at <https://aerobasegroup.com/nsn/5905-01-062-4440>

Section Quantity:

1

Body Diameter:

Between 1.032 inches and 1.156 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

Between 0.709 inches and 0.777 inches

Mounting Bushing Length:

Between 0.344 inches and 0.390 inches

Body Length:

Between 0.468 inches and 0.750 inches

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing w/panel seal and standard bushing w/shaft seal

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0