NSN 5905-01-064-4029

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-064-4029

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.3750 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.400 inches
Undercut Width:
0.0630 inches
Body Diameter:
0.500 inches
Shaft Diameter:
0.0935 inches
Shaft Length:
0.875 inches
Body Length:
1.188 inches
Mounting Lip Diameter:
0.5000 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.50 inch-ounces
Maximum Running Torque:
0.30 inch-ounces
Maximum Stop Torque:
20.00 inch-ounces
Shaft End Play:

0.005 inches

NSN 5905-01-064-4029

Shaft Runout:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.003 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
1.0
Fragility Factor:
Moderately rugged
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Features Provided:
Hermetically sealed
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold

NSN 5905-01-064-4029

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0