

View Online at <https://aerobasegroup.com/nsn/5905-01-064-4687>

Section Quantity:

1

Body Style:

Rectangular w/bushing

Reliability Indicator:

Not established

First Flat Length:

Between 0.303 inches and 0.345 inches

Flat Height:

0.156 inches

Shaft Diameter:

Between 0.248 inches and 0.250 inches

Shaft Length:

Between 2.095 inches and 2.170 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.469 inches

Body Width:

1.000 inches

Body Height:

0.956 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

290.0

Nonturn Device Location:

At 3 oclock

Nonturn Device Radius:

Between 0.428 inches and 0.480 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

316.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 heat sink single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0