Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-064-5675

Section	Quantity:
---------	-----------

1

Body Style:

Cylindrical

**Reliability Indicator:** 

Not established

#### **Terminal Length:**

0.187 inches

**Body Diameter:** 

0.250 inches

**Body Length:** 

0.180 inches

Actuator Type:

Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

240.0

#### Center To Center Distance Between Terminals:

0.200 inches

**Terminal Location:** 

Rear end

Mounting Method:

Terminal

**Electrical Resistance Per Section:** 

250.0 ohms single section

#### **Rotary Actuator Travel In Angular Deg:**

350.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

# Actuator Travel Control Feature:

Stops

# Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

### Standard Taper Curve Per Section:

A single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0