Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-064-5679

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.875 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.810 inches

## Mounting Bushing Length:

0.310 inches

## Body Length:

# 1.000 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Screw Thread Diameter:

0.375 inches

#### Screw Thread Series Designator:

Unef

#### Screw Thready Qty Per Inch (tpi):

32.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

#### Mounting Method:

Standard bushing

#### **Electrical Resistance Per Section:**

5.0 kilohms single section

#### Function Conformity Tolerance Per Section:

-0.30/+0.30 single section

#### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Power Dissipation Rating Per Section In Watts:

1.5 free air single section

#### **Function Conformity Per Section:**

Single section independent linearity

#### **Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 single section

# NSN 5905-01-064-5679

Precision Nonwire Wound Variable Resistor - Page 2 of 2



**Function Characteristic Per Section:** 

Single section linear

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

# Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

#### Fiig:

A002a0