## NSN 5905-01-064-9036

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-064-9036

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:                |
|--|
| -260.0/+260.0  |
| Electrical Resistance:   |
| 540.000 ohms   |
| Resistance Tolerance In Percent:   |
| -5.000/+5.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:                      |
| 40.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:              |
| 350.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:                 |
| -55.0/+350.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Tab, solder lug  |
| Reliability Indicator:   |
| Not established  |
| Body Length:   |
| 6.000 inches   |
| Body Width:  |
| 1.000 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 6.750 inches   |
| Power Dissipation Rating In Watts:   |
| 75.000 free air  |
| Terminal Width:  |
| 0.188 inches   |
| End Application:   |
| Forrestal class cv, strategic weapon systems (poseidon and trident).         |
| Mounting Hole Size:  |
| 0.196 inches   |
| Criticality Code Justification:  |
| Feat   |
| Special Features:  |
| Weapon system essential  |
| Style Designator:  |
| Terminals one edge   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |

--

## NSN 5905-01-064-9036

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0