## NSN 5905-01-064-9074

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-064-9074 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.125 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.594 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 270.0 **Nonturn Device Location:** At 3 oclock **Nonturn Device Radius:** 0.531 inches **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing

Electrical Resistance Per Section: 8.0 ohms single section Rotary Actuator Travel In Angular Deg:

300.0

## NSN 5905-01-064-9074

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



## Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No