## NSN 5905-01-064-9096

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-064-9096

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.188 inches
Body Length:
0.298 inches
Body Width:
0.450 inches
Body Height:
0.430 inches
Actuator Type:
Flush drive with slot-hole
Center To Center Distance Between Terminals:
0.310 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
1.000 megohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.155 inches
Ambient Tempurature In Day Calaine Day Castien At Zara Bareant Batad Barrary
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
125.0 single section
125.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
125.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section
125.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section  Power Dissipation Rating Per Section In Watts:
125.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section  Power Dissipation Rating Per Section In Watts: 0.5 free air single section
125.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section  Power Dissipation Rating Per Section In Watts: 0.5 free air single section  Resistance Tolerance Per Section In Percent:
125.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section  Power Dissipation Rating Per Section In Watts: 0.5 free air single section  Resistance Tolerance Per Section In Percent: -20.0/+20.0 single section
125.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section  Power Dissipation Rating Per Section In Watts: 0.5 free air single section  Resistance Tolerance Per Section In Percent: -20.0/+20.0 single section  Actuator Travel Control Feature:
125.0 single section  Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section  Power Dissipation Rating Per Section In Watts: 0.5 free air single section  Resistance Tolerance Per Section In Percent: -20.0/+20.0 single section  Actuator Travel Control Feature:  Stops

A single section

## NSN 5905-01-064-9096

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
F!!

A002a0