NSN 5905-01-064-9675

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-064-9675

| 2 |
|---|
| Body Style: |
| Cylindrical bushing mounted |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 1.094 inches |
| Shaft Diameter: |
| Between 0.248 inches and 0.251 inches |
| Shaft Length: |
| 0.875 inches |
| Mounting Bushing Length: |
| 0.375 inches |
| Body Length: |
| 1.266 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Nonturn Device Location: |
| At 9 oclock |
| Nonturn Device Radius: |
| 0.531 inches |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Standard bushing |
| Electrical Resistance Per Section: |
| 5.000 kilohms all sections |
| Rotary Actuator Travel In Angular Deg: |
| Between 309.0 and 320.0 |
| Resistance Tempurature Characteristic Range Per Section In Percent: |
| -3.0/+0.0 -55 degrees celsius all sections and -5.0/+10.0 -25 degrees celsius all sections and -5.0/+10.0 25 degrees celsius all sections and |

120.0 all sections

+0.0/+3.0 120 degrees celsius all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

NSN 5905-01-064-9675

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Power Dissipation Rating Per Section In Watts: |
|---|
| 2.0 free air all sections |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 all sections |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 all sections |
| Standard Taper Curve Per Section: |
| A all sections |
| Test Data Document: |
| 81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 6 tab, solder lug |
| Specification Data: |
| 81349-mil-r-94/6 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |