## NSN 5905-01-065-0381

**Section Quantity:** 

**Body Style:** 

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-065-0381

200,000
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
Between 0.495 inches and
Shaft Diameter:
Between 0.1248 inches and 0.1251 inches
Shaft Length:
Between 0.690 inches and 0.710 inches
Mounting Bushing Length:
Between 0.245 inches and 0.255 inches
Body Length:
Between 0.300 inches and 0.310 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Maximum Starting Torque:
12.00 inch-ounces
Maximum Running Torque:
12.00 inch-ounces
Maximum Stop Torque:
80.00 inch-ounces
Nonturn Device Location:
At 6 oclock
Nonturn Device Radius:
Between 0.133 inches and 0.136 inches
Shaft End Play:
0.006 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.002 inches

## NSN 5905-01-065-0381

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.003 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Hermetically sealed
Cubic Measure:
0.060 cubic inches
Electrical Resistance Per Section:
500.0 ohms single section
Rotary Actuator Travel In Angular Deg:
330.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Unpackaged Unit Weight:
2.84 grams
2.84 grams  Terminal Type And Quantity:

3 turret

## NSN 5905-01-065-0381

Precision Wire Wound Variable Resistor - Page 3 of 3



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0