NSN 5905-01-065-4069

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-065-4069

view Offiline at https://aerobasegroup.com/hsh/5505-01-005-4005
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-200.0/+200.0
Electrical Resistance:
5.600 kilohms
Resistance Tolerance In Percent:
-5.000/+5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
16
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
0.120 inches
Dody Longth.
Body Length:
Between 0.840 inches and 0.880 inches
Between 0.840 inches and 0.880 inches
Between 0.840 inches and 0.880 inches Body Width:
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height:
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches Schematic Diagram Designator:
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts:
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.000 total network
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.000 total network Terminal Width:
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.000 total network Terminal Width: Between 0.015 inches and 0.020 inches
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.000 total network Terminal Width: Between 0.015 inches and 0.020 inches Identical Value Resistor Quantity:
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.000 total network Terminal Width: Between 0.015 inches and 0.020 inches Identical Value Resistor Quantity: 15 each resistor
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.000 total network Terminal Width: Between 0.015 inches and 0.020 inches Identical Value Resistor Quantity: 15 each resistor Maximum Tolerance Deviation In Percent:
Between 0.840 inches and 0.880 inches Body Width: Between 0.290 inches and 0.310 inches Body Height: 0.200 inches Schematic Diagram Designator: Ladder network Power Dissipation Rating In Watts: 2.000 total network Terminal Width: Between 0.015 inches and 0.020 inches Identical Value Resistor Quantity: 15 each resistor Maximum Tolerance Deviation In Percent: -0.05/+0.05

N/a

NSN 5905-01-065-4069

Film Fixed Resistor Network - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0