NSN 5905-01-065-8332

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-065-8332

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.495 mils and 0.505 centimeters
Shaft Diameter:
Between 0.1248 inches and 0.1251 inches
Shaft Length:
Between 0.690 inches and 0.710 inches
Mounting Bushing Length:
Between 0.245 inches and 0.255 inches
Body Length:
Between 0.300 inches and 0.310 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
320.0
Maximum Starting Torque:
Maximum Starting Torque: 12.00 inch-ounces
12.00 inch-ounces
12.00 inch-ounces Maximum Running Torque:
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque:
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location:
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 6 oclock
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 6 oclock Nonturn Device Radius:
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 6 oclock Nonturn Device Radius: Between 0.133 inches and 0.136 inches
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 6 oclock Nonturn Device Radius: Between 0.133 inches and 0.136 inches Shaft End Play:
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 6 oclock Nonturn Device Radius: Between 0.133 inches and 0.136 inches Shaft End Play: 0.006 inches
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 6 oclock Nonturn Device Radius: Between 0.133 inches and 0.136 inches Shaft End Play: 0.006 inches Shaft Runout:
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 6 oclock Nonturn Device Radius: Between 0.133 inches and 0.136 inches Shaft End Play: 0.006 inches Shaft Runout: 0.003 inches
12.00 inch-ounces Maximum Running Torque: 12.00 inch-ounces Maximum Stop Torque: 80.00 inch-ounces Nonturn Device Location: At 6 oclock Nonturn Device Radius: Between 0.133 inches and 0.136 inches Shaft End Play: 0.006 inches Shaft Runout: 0.003 inches Lateral Runout:

NSN 5905-01-065-8332

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.003 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Cubic Measure:
0.060 cubic inches
Electrical Resistance Per Section:
1.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
330.0
Function Conformity Tolerance Per Section:
-1.00/+1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

NSN 5905-01-065-8332

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0