## NSN 5905-01-066-5441

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-066-5441 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.75000 inches Pilot Length: 0.06200 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.05700 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.500 inches **Body Length:** 0.700 inches **Mounting Lip Diameter:** 0.87500 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 354.0 **Maximum Starting Torque:** 0.20 inch-ounces **Maximum Running Torque:** 

0.20 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.0015 inches

## NSN 5905-01-066-5441

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.00200 inches
Shaft Radial Play:
0.003 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
1.000 kilohms single section
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
180.0 single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-2.0/+2.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5905-01-066-5441

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0