## NSN 5905-01-066-7104

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-066-7104

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.188 inches
Shaft Diameter:
0.090 inches
Shaft Length:
0.062 inches
Body Length:
0.375 inches
Body Width:
0.188 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
2.000 inches
End Application:
Wsr-74c radar, lwr
Terminal Location:
Left adjacent side two rows
Mounting Method:
Terminal
Center To Center Distance Between Terminal Rows:
1.000 inches
Features Provided:
Humidity proof
Electrical Resistance Per Section:
200.000 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
1.000 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
05.0/14.05.0 signals a satism

-25.0/+105.0 single section

## NSN 5905-01-066-7104

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: