Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-067-4617

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Established

**Reliability Failure Rate Level In Percent:** 

0.100

**Overall Length:** 

1.308 inches

Terminal Length:

0.500 inches

**Overall Height:** 

0.815 inches

**Overall Width:** 

0.190 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.115 inches

Shaft Length:

0.058 inches

**Body Length:** 

1.250 inches

Body Width:

0.190 inches

**Body Height:** 

0.315 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 6120.0 and 9720.0

Center To Center Distance Between Terminals:

0.700 inches

Fragility Factor:

Moderately delicate

Lateral Distance Between Mounting Hole Centers:

1.000 inches

**Mounting Facility Quantity:** 

A002a0



Terminal Location:	
Lower adjacent side two rows	
Mounting Method:	
Terminal and unthreaded hole	
Center To Center Distance Between Terminal Rows:	
0.100 inches	
Cubic Measure:	
0.075 cubic inches	
Electrical Resistance Per Section:	
10.0 percent, rated amperes c and better flooring	
Rotary Actuator Travel In Angular Deg:	
Between 6120.0 and 9720.0	
Center To Center Distance Between Center Terminal And Outsi	de Terminal:
0.300 inches	
Ambient Tempurature In Deg Celsius Per Section At Zero Perce	ent Rated Power:
150.0 single section	
Tempurature Coefficient Of Resistance Per Section In Ppm Per	Deg Celsius:
-50.0/+50.0 single section	
Power Dissipation Rating Per Section In Watts:	
0.75 7th secondary quality	
Resistance Tolerance Per Section In Percent:	
-5.0/+5.0 single section	
Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated	Power:
85.0 single section	
Standard Taper Curve Per Section:	
A single section	
Test Data Document:	
81349-mil-r-39015 specification (includes engineering type bulletins	, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and si	milar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions th	at are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:	
3 pin	
Specification Data:	
81349-mil-r-39015/1 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	
Fiig:	