NSN 5905-01-068-4582

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-068-4582

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Terminal Length:
0.300 inches
Shaft Diameter:
Between 0.060 inches and 0.090 inches
Shaft Length:
0.050 inches
Body Length:
Between 0.230 inches and 0.270 inches
Body Width:
Between 0.145 inches and 0.185 inches
Body Height:
Between 0.230 inches and 0.270 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Center To Center Distance Between Terminals:
0.200 inches
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section

NSN 5905-01-068-4582

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:	
Clutch	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
85.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 pin	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	