NSN 5905-01-068-9319

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-068-9319 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.785 inches **Body Length:** 0.422 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Fragility Factor:** Moderately delicate **Terminal Location:** Front end **Mounting Method:** Tab **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 120.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 heat sink single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** 0.438 in.Long knob secured to drive cross slot

Terminal Type And Quantity: 2 tab, solder lug

NSN 5905-01-068-9319

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0