Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-068-9768

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

### Reliability Indicator:

Not established

### **Body Diameter:**

3.062 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.500 inches

#### Mounting Bushing Length:

0.250 inches

#### Body Length:

4.125 inches

### Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

#### Nonturn Device Location:

At 9 oclock

### Nonturn Device Radius:

0.438 inches

#### Screw Thread Diameter:

0.250 inches

#### **Screw Thread Series Designator:**

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Rear end

# Mounting Method:

Standard bushing

# Features Provided:

Hermetically sealed

# **Electrical Resistance Per Section:**

1.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

9000.0



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 175.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -25.0/+25.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A002a0