NSN 5905-01-069-1533

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-069-1533 **Section Quantity: Body Style:** Cylindrical w/readout **Reliability Indicator:** Not established **Terminal Length:** 0.187 inches **Body Diameter:** 1.375 inches **Mounting Bushing Length:** 0.281 inches **Body Length:** 2.015 inches **Actuator Type:** Integral knob with counter **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 15.00 inch-ounces **Maximum Running Torque:** 15.00 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Terminal Location:** Rear end **Mounting Method:** Clamp ring and flange **Electrical Resistance Per Section:** 2.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 85.0 single section **Power Dissipation Rating Per Section In Watts:** 2.5 free air single section **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Continuous motion

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section

NSN 5905-01-069-1533

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire loop

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0