

View Online at <https://aerobasegroup.com/nsn/5905-01-069-2726>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Terminal Length:

0.547 inches

First Flat Length:

0.250 inches

Flat Height:

0.094 inches

Body Diameter:

0.500 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.500 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Mechanical Backlash In Deg Angular Rotation:

3.0

Center To Center Distance Between Terminals:

0.200 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

25.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

295.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0 to 8.7 -55 degrees celsius single section and +0.0 to 4.4 -25 degrees celsius single section and +0.0 to 2.5 0 degrees celsius single section and -3.1 to 3.1 85 degrees celsius single section and +0.0 to 6.9 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0