## NSN 5905-01-069-3828

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-069-3828 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.500 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 25000.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Maximum Stop Torque:** 1.00 inch-ounces **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:** 0.001 inches **Shaft Radial Play:** 0.002 inches **Fragility Factor:** Moderately rugged

**Screw Thread Diameter:** 0.250 inches

## NSN 5905-01-069-3828

A002a0

Precision Wire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
100.0 ohms single section
Rotary Actuator Travel In Angular Deg:
25000.0
Function Conformity Tolerance Per Section:
-0.10/+0.10 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section absolute linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Clutch
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Test Data Document:
81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 turret
Specification Data:
81349-mil-r-12934/31 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: