Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-069-4993

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.250 inches

Body Length:

1.500 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

25000.0

Maximum Starting Torque:

1.50 inch-ounces

Maximum Running Torque:

1.00 inch-ounces

Maximum Stop Torque:

1.00 inch-ounces

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.002 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches



Precision Wire Wound Variable Resistor - Page 2 of 2 **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 5.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 25000.0 **Function Conformity Tolerance Per Section:** -0.10/+0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section absolute linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Clutch **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Test Data Document:** 81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 turret **Specification Data:** 81349-mil-r-12934/31 government specification Shelf Life: Unit Of Measure: **Demilitarization:**

No Fiig:

N/a

A002a0