

View Online at <https://aerobasegroup.com/nsn/5905-01-069-5217>

Section Quantity:

1

Body Style:

Rectangular w/tab/flange mounted

Reliability Indicator:

Not established

Mounting Hole Diameter:

Between 0.183 inches and 0.190 inches

Body Length:

Between 9.115 inches and 9.135 inches

Body Width:

Between 0.990 inches and 1.010 inches

Body Height:

1.250 inches

Shaft Bearing Type:

Bearing

Actuator Type:

Slider

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Longitudinal Actuator Effective Electrical Stroke Length:

7.000 inches

Fragility Factor:

Moderately rugged

Distance Between Mounting Hole Centers:

Between 1.677 inches and 1.697 inches

Lateral Distance Between Mounting Hole Centers:

Between 8.990 inches and 9.010 inches

Mounting Facility Quantity:

4

Terminal Location:

Left adjacent side single row

Mounting Method:

Unthreaded hole

Features Provided:

Humidity proof

Electrical Resistance Per Section:

10.0 kilohms single section

Function Conformity Tolerance Per Section:

-0.20/+0.20 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Tap Location From Ccw Terminal Per Section In Ohms:

5000.0 single section

Function Characteristic Per Section:

Single section linear

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0