Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-069-5623

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.100

Overall Length:

1.308 inches

Terminal Length:

0.500 inches

Overall Height:

0.815 inches

Overall Width:

0.190 inches

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.115 inches

Shaft Length:

0.058 inches

Body Length:

1.250 inches

Body Width:

0.190 inches

Body Height:

0.315 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 6120.0 and 9720.0

Center To Center Distance Between Terminals:

0.700 inches

Fragility Factor:

Moderately delicate

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:



Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal and unthreaded hole
Center To Center Distance Between Terminal Rows:
0.100 inches
Electrical Resistance Per Section:
50.0 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 6120.0 and 9720.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.75 7th secondary quality
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-39015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
81349-mil-r-39015/1 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0

A002a0