## NSN 5905-01-069-6760

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-069-6760 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** Between 0.927 inches and **Shaft Diameter:** 0.156 inches **Shaft Length:** Between 0.677 inches and 0.697 inches **Body Length:** Between 0.568 inches and 0.588 inches **Shaft Style:** Round, slotted, knurled **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Fragility Factor:** Moderately rugged **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Tab **Electrical Resistance Per Section:** 10.0 megohms single section

**Rotary Actuator Travel In Angular Deg:** 300.0 **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

## NSN 5905-01-069-6760

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A002a0