Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-069-7139

## Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

## **Reliability Indicator:**

Not established

#### Mounting Hole Diameter:

0.093 inches

#### Shaft Diameter:

0.115 inches

- Shaft Length:
- 0.058 inches

Body Length:

1.250 inches

### Body Width:

0.190 inches

### **Body Height:**

0.315 inches

Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

9000.0

#### Lateral Distance Between Mounting Hole Centers:

1.000 inches

#### **Mounting Facility Quantity:**

2

#### **Terminal Location:**

Lower adjacent side single row

#### **Mounting Method:**

Unthreaded hole

#### **Electrical Resistance Per Section:**

30.000 kilohms single section

#### Rotary Actuator Travel In Angular Deg:

9000.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section



### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

#### Actuator Travel Control Feature:

Clutch

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

**Demilitarization:** 

No

Fiig:

A002a0