Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-070-3541

# Section Quantity:

1

Body Style:

Cylindrical

# **Reliability Indicator:**

Not established

### **Body Diameter:**

0.625 inches

#### **Body Length:**

0.312 inches

#### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

280.0

#### **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Tab

### **Electrical Resistance Per Section:**

1.000 kilohms single section

# Rotary Actuator Travel In Angular Deg:

300.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

### Power Dissipation Rating Per Section In Watts:

0.25 heat sink single section

### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

### Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

### **Standard Taper Curve Per Section:**

A single section

### **Special Features:**

0.750 in. Long rear shaft

### **Terminal Type And Quantity:**

3 tab, solder lug

Shelf Life:

N/a

### Unit Of Measure:

--



Demilitarization:

No

Fiig:

A002a0