NSN 5905-01-071-1832

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-071-1832

Section Quantity: Body Style: Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Body Diameter:** 0.450 inches **Body Length:** 0.315 inches **Actuator Type:** Integral knob **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Maximum Stop Torque:** 15.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Fragility Factor:** Moderately delicate **Terminal Location:** Rear end **Mounting Method: Terminal Features Provided:** Humidity proof **Electrical Resistance Per Section:** 500.0 ohms c and better flooring **Rotary Actuator Travel In Angular Deg:** 310.0 **Center To Center Distance Between Center Terminal And Outside Terminal:** 0.100 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

NSN 5905-01-071-1832

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Immersion sealed
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0