Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-071-6639

## Section Quantity:

2

Body Style: Cylindrical bushing mounted Reliability Indicator:

Not established

**Body Diameter:** 

1.094 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

### 1.266 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

### **Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:** 

500.000 kilohms all sections

### Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

### Resistance Tempurature Characteristic Range Per Section In Percent:

-3.0/+0.0 -55 degrees celsius all sections and -5.0/+10.0 -25 degrees celsius all sections and -5.0/+10.0 25 degrees celsius all sections and

+0.0/+3.0 120 degrees celsius all sections

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

# NSN 5905-01-071-6639 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



### **Power Dissipation Rating Per Section In Watts:**

2.0 free air all sections

#### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

### Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

### Standard Taper Curve Per Section:

A all sections

#### **Test Data Document:**

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

6 tab, solder lug

#### **Specification Data:**

81349-mil-r-94/6 government specification

Shelf Life:

N/a

Unit Of Measure:

# --

Demilitarization:

No

# Fiig:

A002a0