Nonprecision Wire Wound Variable Resistor - Page 1 of 2



Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.086 inches

Shaft Diameter:

0.125 inches

- Shaft Length:
- 0.030 inches

Body Length:

1.250 inches

Body Width:

0.250 inches

Body Height:

0.312 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

7.50 inch-ounces

Maximum Running Torque:

7.50 inch-ounces

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

10.000 ohms single section

Rotary Actuator Travel In Angular Deg:

2250.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section



NSN 5905-01-072-2138

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0