Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-072-3243

# Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.190 inches

#### Shaft Diameter:

0.090 inches

#### Shaft Length:

0.040 inches

#### **Body Length:**

0.375 inches

#### Body Width:

0.150 inches

# Body Height:

0.375 inches

# Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

7560.0

### **Center To Center Distance Between Terminals:**

0.200 inches

### **Terminal Location:**

Rear end

### **Mounting Method:**

Terminal

### **Electrical Resistance Per Section:**

10.000 kilohms single section

### **Rotary Actuator Travel In Angular Deg:**

7560.0

## Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

## Power Dissipation Rating Per Section In Watts:

0.75 free air single section



**Resistance Tolerance Per Section In Percent:** 

-5.0/+5.0 single section

## Actuator Travel Control Feature:

Clutch

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0