## NSN 5905-01-072-3832

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-072-3832 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.3750 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 0.375 inches **Undercut Width:** 0.0630 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.0935 inches **Shaft Length:** 0.375 inches **Body Length:** 1.187 inches **Mounting Lip Diameter:** 0.5000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 

0.30 inch-ounces **Maximum Stop Torque:** 

20.00 inch-ounces

**Shaft End Play:** 0.005 inches

## NSN 5905-01-072-3832

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Runout:
0.003 inches
Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Electrical Resistance Per Section:
10.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:

1 tab, solder lug and 2 turret

## NSN 5905-01-072-3832

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0