NSN 5905-01-073-1224

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-073-1224 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 2.000 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 0.906 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.846 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 1.200 inches **Shaft End Play:** 0.003 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.004 inches **Pilot Diameter Runout:** 0.060 inches

Shaft Radial Play:

0.004 inches

NSN 5905-01-073-1224

Precision Wire Wound Variable Resistor - Page 2 of 3



| Fragility Factor: |
|--|
| Moderately rugged |
| Screw Thread Diameter: |
| 0.375 inches |
| Screw Thread Series Designator: |
| Unef |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Terminal Location: |
| Radially positioned over less than half the circumference |
| Mounting Method: |
| Standard bushing |
| Features Provided: |
| Humidity proof |
| Electrical Resistance Per Section: |
| 5.0 percent, rated amperes c and better flooring |
| Rotary Actuator Travel In Angular Deg: |
| 350.0 |
| Function Conformity Tolerance Per Section: |
| -0.30/+0.30 single section |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 4.0 7th secondary quality |
| Function Conformity Per Section: |
| Single section independent linearity |
| Resistance Tolerance Per Section In Percent: |
| -3.0/+3.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Function Characteristic Per Section: |
| 7 oclock all primaries |
| Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: |
| -20.0/+20.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Precious Material And Location: |
| Terminal surfaces gold |
| Precious Material: |
| Gold |
| Terminal Type And Quantity: |
| 3 turret |
| Shelf Life: |
| N/a |

NSN 5905-01-073-1224

Precision Wire Wound Variable Resistor - Page 3 of 3



| ш | ın | 10 | <i>(</i>)+ | Measure: | |
|---|----|----|-------------|----------|--|
| | | | | | |

--

Demilitarization:

No

Fiig:

A002a0