

View Online at <https://aerobasegroup.com/nsn/5905-01-073-1907>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

Between 0.235 inches and 0.265 inches

Flat Height:

Between 0.092 inches and 0.096 inches

Body Diameter:

Between 0.484 inches and 0.516 inches

Shaft Diameter:

Between 0.124 inches and 0.126 inches

Shaft Length:

Between 0.335 inches and 0.345 inches

Mounting Bushing Length:

Between 0.370 inches and 0.402 inches

Body Length:

Between 0.613 inches and 0.623 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear-bottom

Mounting Method:

Locking bushing w/shaft seal

Electrical Resistance Per Section:

2.500 kilohms single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0