Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-073-4157

	a mups.//aerobasegroup.com/nsn/5905-01-073-4157
Section Qu	iantity:
1	
Body Style	:
Cylindrical	
Reliability	Indicator:
Not establis	hed
Body Diam	leter:
0.785 inche	S
Body Leng	th:
0.391 inche	S
Actuator T	ype:
Flush drive	with slot-hole
Effective E	lectrical Rotation In Deg Angular Rotation:
270.0	
Maximum \$	Starting Torque:
4.00 inch-ou	unces
Maximum F	Running Torque:
4.00 inch-ou	unces
Fragility Fa	actor:
Moderately	rugged
Terminal L	ocation:
Rear end	
Mounting M	Method:
Terminal	
Features P	rovided:
Humidity pr	oof
Electrical F	Resistance Per Section:
5.000 ohms	s single section
Rotary Act	uator Travel In Angular Deg:
270.0	
Ambient Te	empurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single	e section
Tempuratu	re Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0	single section
Power Diss	sipation Rating Per Section In Watts:
1.5 free air	single section
Resistance	e Tolerance Per Section In Percent:
-20.0/+20.0	single section
Actuator T	ravel Control Feature:
Stops	
Ambient Te	empurature In Deg Celsius Per Section At Full Rated Power:
55.0 single	section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0