NSN 5905-01-073-4547

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-073-4547

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
First Flat Length:
0.400 inches
Flat Height:
Between 0.210 inches and 0.220 inches
Body Diameter:
Between 1.960 inches and 1.980 inches
Shaft Diameter:
Between 0.245 inches and 0.255 inches
Shaft Length:
Between 0.530 inches and 0.540 inches
Mounting Bushing Length:
Between 0.330 inches and 0.340 inches
Body Length:
Between 2.220 inches and 2.240 inches
Shaft Style:
Round, flatted
Actuator Type:
Double ended shaft
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.000 kilohms single section
Function Conformity Tolerance Per Section:
-2.00/+2.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
105.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section

NSN 5905-01-073-4547

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Function Conformity Per Section:
Single section terminal base linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
13 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No