NSN 5905-01-073-8844

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-073-8844 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.844 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 2.094 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Maximum Stop Torque:** 160.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.005 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:**

0.001 inches **Shaft Radial Play:** 0.002 inches

NSN 5905-01-073-8844

Precision Wire Wound Variable Resistor - Page 2 of 3



Mechanical Backlash In Deg Angular Rotation:

0.5

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

20.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.05/+0.05 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-260.0/+260.0 single section

Power Dissipation Rating Per Section In Watts:

5.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-1.0/+1.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Test Data Document:

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 turret

Specification Data:

81349-mil-r-12934/32 government specification

Shelf Life:

NSN 5905-01-073-8844

Precision Wire Wound Variable Resistor - Page 3 of 3



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0