## NSN 5905-01-073-8846

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-073-8846 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.844 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.251 inches **Body Length:** 2.094 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Maximum Stop Torque:** 160.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.562 inches

**Shaft End Play:** 0.005 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:** 0.001 inches **Shaft Radial Play:** 0.002 inches

## NSN 5905-01-073-8846

Precision Wire Wound Variable Resistor - Page 2 of 3



## Mechanical Backlash In Deg Angular Rotation:

0.5

**Fragility Factor:** 

Moderately rugged

**Screw Thread Diameter:** 

0.375 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

2.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:** 

3600.0

**Function Conformity Tolerance Per Section:** 

-0.05/+0.05 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:** 

5.0 free air single section

**Function Conformity Per Section:** 

Single section independent linearity

**Resistance Tolerance Per Section In Percent:** 

-1.0/+1.0 single section

**Actuator Travel Control Feature:** 

Stops

**Function Characteristic Per Section:** 

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Test Data Document:** 

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

3 turret

**Specification Data:** 

81349-mil-r-12934/32 government specification

Shelf Life:

## NSN 5905-01-073-8846

Precision Wire Wound Variable Resistor - Page 3 of 3



| ш | ın | 10 | <i>(</i> )+ | Measure: |  |
|---|----|----|-------------|----------|--|
|   |    |    |             |          |  |

--

Demilitarization:

No

Fiig:

A002a0