Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-075-0326

# Section Quantity:

1

Body Style:

Rectangular w/mounting hole/slot

# **Reliability Indicator:**

Not established

## **Terminal Length:**

0.187 inches

## **Body Length:**

0.405 inches

#### **Body Width:**

0.235 inches

## Body Height:

0.375 inches

#### Actuator Type:

Flush drive with slot-hole

# Maximum Starting Torque:

5.00 inch-ounces

# Maximum Running Torque:

5.00 inch-ounces

# Center To Center Distance Between Terminals:

0.200 inches

#### **Terminal Location:**

Left adjacent side two rows

#### Mounting Method:

Terminal

## Center To Center Distance Between Terminal Rows:

0.100 inches

## **Electrical Resistance Per Section:**

50.0 ohms single section

## **Rotary Actuator Travel In Angular Deg:**

8280.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

# Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

# Power Dissipation Rating Per Section In Watts:

0.7 free air single section

# Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

# NSN 5905-01-075-0326

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0