NSN 5905-01-075-4584

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-075-4584 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.3750 inches Pilot Length: 0.0620 inches **Overall Length:** 0.828 inches **Undercut Diameter:** 0.375 inches **Undercut Width:** 0.0570 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.093 inches **Shaft Length:** 0.312 inches **Body Length:** 0.500 inches **Overall Diameter:** 0.500 inches **Mounting Lip Diameter:** 0.5000 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:**

Maximum Running Torque:

0.20 inch-ounces

0.20 inch-ounces

NSN 5905-01-075-4584

Precision Wire Wound Variable Resistor - Page 2 of 3



Maximum Stop Torque:
80.00 inch-ounces
Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.001 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.30/+0.30 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
80.0 single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a

NSN 5905-01-075-4584

Precision Wire Wound Variable Resistor - Page 3 of 3



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0