## NSN 5905-01-075-7958

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-075-7958

Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.594 inches
Body Diameter:
0.781 inches
Body Length:
0.391 inches
Overall Diameter:
0.781 inches
Actuator Type: Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation: 270.0
Fragility Factor:
Moderately delicate  Terminal Location:
Rear end
Mounting Method:  Terminal
Features Provided:
Humidity proof  Electrical Resistance Per Section:
1.0 ohms single section
Rotary Actuator Travel In Angular Deg:
270.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
180.0 single section
Power Dissipation Rating Per Section In Watts:
3.0 heat sink single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops  Tomography Coefficient Of Resistance Wire Per Section to Per Per Per Coloine
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

## NSN 5905-01-075-7958

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0