

View Online at <https://aerobasegroup.com/nsn/5905-01-075-8894>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

Between 0.605 inches and 0.635 inches

Flat Height:

Between 0.123 inches and 0.127 inches

Body Diameter:

0.625 inches

Shaft Diameter:

Between 0.154 inches and 0.157 inches

Shaft Length:

1.125 inches

Body Length:

0.391 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

270.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Terminal

Electrical Resistance Per Section:

1.000 megohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+9.0 -55 degrees celsius single section and +0.0/+8.0 -40 degrees celsius single section and +0.0/+2.5 0 degrees celsius single section and -3.5/+3.5 85 degrees celsius single section and -5.5/+5.5 105 degrees celsius single section and -7.0/+7.0 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Special Features:

One terminal protruding from rear end

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0