NSN 5905-01-076-6296

Section Quantity:

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-076-6296

Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.456 inches
Body Diameter:
0.677 inches
Shaft Diameter:
Between 0.124 inches and 0.126 inches
Shaft Length:
Between 0.594 inches and 0.656 inches
Mounting Bushing Length:
Between 0.234 inches and 0.266 inches
Body Length:
0.625 inches
Overall Diameter:
0.901 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Switch Voltage Rating In Volts:
250.0 and 125.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Nonturn Device Location:
At 3 oclock
Nonturn Device Radius:
Between 0.297 inches and 0.328 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef

NSN 5905-01-076-6296

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
325.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+5.5 -55 degrees celsius single section and +0.0/+4.0 -40 degrees celsius single section and +0.0/+2.0 0 degrees celsius single section
and -2.5/+2.5 85 degrees celsius single section and -3.0/+3.0 105 degrees celsius single section and -4.0/+4.0 120 degrees celsius single
section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 heat sink single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
3.000 ac and 1.000 dc
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0