Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-076-8037

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

1.563 inches

Flat Height:

0.344 inches

Body Diameter:

12.000 inches

Shaft Diameter:

0.375 inches

Shaft Length:

2.000 inches

Body Length:

3.000 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unc

Screw Thready Qty Per Inch (tpi):

20.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Electrical Resistance Per Section:

10.0 ohms c and better flooring

Power Dissipation Rating Per Section In Watts:

1000.0 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0