NSN 5905-01-076-9399

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-076-9399 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.455 inches **Terminal Length:** 0.300 inches **Overall Height:** 0.720 inches **Overall Width:** 0.200 inches

Shaft Diameter: 0.075 inches **Shaft Length:** 0.080 inches **Body Length:**

0.375 inches **Body Width:** 0.200 inches **Body Height:** 0.420 inches

Shaft Style: Round, slotted **Actuator Type:** Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

9000.0

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor: Moderately delicate

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Features Provided:

Humidity proof

Electrical Resistance Per Section:

50.0 percent, rated amperes c and better flooring

NSN 5905-01-076-9399

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
mmersion sealed
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
4002a0