NSN 5905-01-077-3062

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-077-3062

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Cylindrical friction mounted |
| Reliability Indicator: |
| Not established |
| Body Diameter: |
| 0.780 inches |
| Shaft Diameter: |
| 0.250 inches |
| Shaft Length: |
| 1.000 inches |
| Body Length: |
| 0.280 inches |
| Shaft Style: |
| Round |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 240.0 |
| Nonturn Device Location: |
| At 9 oclock |
| Nonturn Device Radius: |
| 0.380 inches |
| Terminal Location: |
| Longitudinally positioned on the circumference |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 20.000 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 240.0 |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -150.0/+150.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 2.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -10.0/+10.0 single section |
| Actuator Travel Control Feature: |

Stops

NSN 5905-01-077-3062

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
|---|
| 65.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 tab, solder lug |
| Shelf Life: |
| N/a |

Demilitarization:

Unit Of Measure:

No

Fiig:

A002a0