Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-077-6289

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

#### **Electrical Resistance:**

1.000 kilohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

### Hermetically sealed

### **Terminal Quantity:**

16

### **Terminal Type:**

Pin

# Reliability Indicator:

Not established

# **Terminal Length:**

0.135 inches

### Body Length:

0.830 inches

#### **Body Width:**

0.270 inches

#### **Body Height:**

0.200 inches

Schematic Diagram Designator:

Ladder network

**Power Dissipation Rating In Watts:** 

1.500 total network

#### **Identical Value Resistor Quantity:**

15 each resistor

#### Style Designator:

Dual inline

#### **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-r-83401/2 government specification

# Shelf Life:

N/a

Film Fixed Resistor Network - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0