## NSN 5905-01-077-8288

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-077-8288 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Overall Length:** 0.675 inches **Terminal Length:** 0.300 inches **Overall Height:** 0.420 inches **Overall Width:** 0.375 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.080 inches **Body Length:** 0.375 inches **Body Width:** 0.170 inches **Body Height:** 0.420 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 5400.0 and 10800.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Fragility Factor:** 

Moderately delicate

Terminal Location:

Lower adjacent side single row

## NSN 5905-01-077-8288

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Mounting Method:   |
|--|
| Terminal   |
| Cubic Measure:   |
| 0.028 cubic inches   |
| Electrical Resistance Per Section:   |
| 20.0 ohms c and better flooring  |
| Rotary Actuator Travel In Angular Deg:   |
| 9000.0   |
| Center To Center Distance Between Center Terminal And Outside Terminal:  |
| 0.100 inches   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:  |
| 150.0 single section   |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:  |
| -50.0/+50.0 single section   |
| Power Dissipation Rating Per Section In Watts:   |
| 0.75 7th secondary quality   |
| Resistance Tolerance Per Section In Percent:   |
| -5.0/+5.0 single section   |
| Actuator Travel Control Feature:   |
| Clutch   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:  |
| 85.0 single section  |
| Standard Taper Curve Per Section:  |
| A single section   |
| Test Data Document:  |
| 81349-mil-r-39015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Terminal Type And Quantity:  |
| 3 pin  |
| Specification Data:  |
| 81349-mil-r-39015/3 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del>-</del>   |
| Demilitarization:  |
| No   |
| Fiig:  |
| A002a0   |
|  |